



DigiLinX Integration Partner Quick Reference Guide

| IP Amplifiers | |
|--|---|
|  | NNP01, NNP02, NNP02-DC |
| IP Speakers | |
|  | IP-Ready - LC265i-IP (in-wall), LC80i-IP (in-ceiling), SC80ipr (in ceiling)* and SC85ipr (in-wall)*. *Requires SL250 or SL254 |
|  | IWTS-4 LCR-IP, IWTS-7 LCR-IP, IWTS-14 LCR-IP, ICTS – 6.1 - IP Require SL250 or SL254 for IP operation. Can be used as conventional passive speaker with other NetStreams models. |
| Music Servers | |
|  | All Audio ReQuest Models |
|  | Fireball: SE-80, E-40, E-120, E2-40, E2-100, E2-200, E2-160, E2-300, DVDM-300, DVDM-552, MX752, MX531, MX311, MX111, AVX-552, AVX-331, AVX-211, Vision |
|  | SoundServer MKII S2000, S3000 – MS5000 and MS1 (audio only) |
|  | NS01, NS02, NS03 |
| Other Music Storage Devices: (via Streaming Music Manager) | |
| PCs or Macs Network Attached Storage Portable MP3 players (via USB) | Windows Media Center USB Mass Storage Devices Cellular Phones (via USB) |
| AM/FM & Satellite Tuners (via MediaLinX) | |
|  PARASOUND | ZTuner (AM/FM Tuner) v1.0 & v.20 |
|  | Xrt12 XM Tuner |
|  | SCH1 (requires SIRS232 cable or the SCH1P2 kit that include the RS232 cable), SCHDOC1P Home Dock |
|  | ST7001 AM/FM/XM Tuner (requires MLA101) |
|  | NNT01, NNT02 |
|  | T-4555 AM/FM/DAB |

Continued

The Ultimate IP A/V Experience



DigiLinX Integration Partner Quick Reference Guide

iPod Docking Stations (via MediaLinX)



To Show Meta-data: IW-4, IW-5, FS-4, FS-5, FS-22
Audio Only: IW-1, IW-2, IW-3, FS-1, FS-2, FS-3



IS201 iPod Dock

Home Cinema Controllers (for use via RS-232 with TheaterLinX, and any others via IR)



SR7001



AVR-3808CI



SoloMovie, AVR350



All current AV Receivers with RS232 support

IP Cameras



BB-HCM331A, BB-HCM381A, BB-HCM371A, BB-HCM311A, KX-HCM250, KX-HCM280, KX-HCM110A, BL-C10, BL-C30A, KX-HCM311A, BB-HCA10A, BB-HCS301A, BB-HCM547A, BB-HCM531A, BB_HCM403A, BB-HCM511A, BB-HCM515A, BB-HCM581A, BB-HCM581A-W

CD Players



CC4001 CD Changer

HVAC Systems (via ControLinX)



8811 Protocol adapter required



Sensible Heat



Use the B+B EIB Medienteknik gateway



Continued

The Ultimate IP A/V Experience



DigiLinX Integration Partner Quick Reference Guide

Lighting Systems (via ControlinX)



Graphic Eye™, RadioRa™, HomeWorks™



InFusion



via DNG232 RS232 interface



via RS232 interface (needs RS485-RS232 converter)



HAI Controller with RS232 interface



via RS232 Interface adapter with power supply



via RS232 interface (PC Node)



Use the B+B EIB Medienteknik Gateway



Automations- und
Steuerungstechnik GmbH



Via RS232 Audio Gateway Driver



Via Evolution Power & Processor Unit and EVO –INT-232 interface



Via Rako RAV232+bidirectional RS232 controller










Continued

The Ultimate IP A/V Experience

main.512.977.9393 / fax.512.977.9398 / 3600 W. Parmer Lane, Suite 100, Austin, TX 78727 / www.netstreams.com



DigiLinX Integration Partner Quick Reference Guide

| Security Systems (via ControlinX) | |
|---|--|
|  | 8811 Protocol adapter required |
|  | Cardio Ile Controller |
|  | Requires DSC IT-100 integration module |
| Cable and Wiring | |
|  | Belden® HomeChoice® 7876A for <i>NetStreams</i> IP-Based Video Belden HomeChoice 7949A for <i>NetStreams</i> IP-Based Audio. |
| Remote Controls | |
|  | RTI IR Remote Controls — Model T1, T1+, T2-C, T3 and M2 Universal Controllers RTI LCD Touch screen Controllers: Model T4 and K4. |
|  | TSU9600, TSU9800 |
| Displays | |
|  | Sharp Plasma – PN – 455RU Sharp LCD – LC-26DA5U, LC-32DA5U |
| Pool/Spa Control | |
|  | Via AquaLink RS Serial Adapter |
| Misc | |
|  | Use NetStreams application |
|  | Use <i>NetStreams</i> Application |

The Ultimate IP A/V Experience

main.512.977.9393 / fax.512.977.9398 / 3600 W. Parmer Lane, Suite 100, Austin, TX 78727 / www.netstreams.com